Desktop Products

G83-6104 Series Business Keyboard



Key Features

- 104 or 105 keys (depending on international layout)
- USB version available with a bus-powered hub for the connection of up to 4 other USB devices.
- Space-efficient compact layout
- Membrane contact switches with rubber-mat technology for individual use
- Reliability:
 MCBF = 1 x 109 operations;
 MTBF > 80 000 hours
- Operating life of individual keys read to more than 20 million operations
- Keycap symbols are wear-resistant and easy to clean

Main Part Numbers

G83-6104LPNEU-0

Light Grey, PS/2, 104 Key Layout

G83-6104LPNEU-2

Black, PS/2, 104 Key Layout

G83-6104LUNEU-0

Light Grey, USB, 104 Key Layout

G83-6104LUNEU-2

Black, USB, 104 Key Layout

Foreign Language Layouts

BE Belgian

CH Swiss

DE German

DK Danish

ES Spanish FR French

GB English (UK)

IT Italian

NO Norwegian

PO Portuguese

SF Swedish/Finnish

*Call for Additional Languages

Other versions available on request.

Color Codes

- -0 Grey housing Grey keys
- -2 Black housing Black keys



Desktop Products

G83-6104 Series Business Keyboard



Technical Data

Power Supply

PS/2 Interface: $+5 \text{ V/DC} \pm 5\%$

USB Interface:

min +4.15 V/DC, max +5.25 V/DC

min +4.75 V/DC, max +5.25 V/DC

Current Input

Interface: PS/2: max. 35 mA USB: typ. 100 mA USB hub: typ. 500 mA

Travel

Total travel: 3.7 mm Pretravel: 2.4 mm Actuation force: 60 cN

Connecting Cable

approx. 1.75 m long with DIN, PS/2 or USB connector

Weight

approx. 1.190 g

Dimensions

458 x 170 x 42 mm (keyboard) approx. 458 x 195 x 42 mm (with USB hub)

Storage Temperature

-20 °C to 60 °C

Operating Temperature

0 °C to 50 °C

Contact

Call, fax or visit our website for more information.

Last Update: 2/15/10

ZF Electronics Corporation

11200 88th Avenue Pleasant Prairie, WI 53158

262.942.6500 Phone: Web: www.cherrycorp.com

keyboardsupport@zf.com E-Mail:

Fax: 262.942.6566 The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice.

Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2008 ZF Electronics Corporation

